CLAIMS:

1.   A method for storing audio-centered information on a unitary storage medium while using a Table-of-Contents (TOC) mechanism for therein specifying an actual configuration of various audio items on said medium,

        being characterized by assigning at least two mutually logically conforming
5   Sub-TOCs to each one of a set of one or more Track Areas, thereby allowing retrieving any constituent Sub-TOC part from at least any correct copy of said Sub-TOCs, and furthermore providing at least one Master-TOC for specifically pointing to each of said Sub-TOCs.

2.   A method as claimed in Claim 1, wherein said Sub-TOCs abut at mutually
10 opposite ends to their associated Track Area.

3.   A method as claimed in Claim 1, wherein the number of sub-TOCs per Track Area is exactly 2.

15 4.   A method as claimed in Claim 1, and furthermore providing any Master-TOC at a standard offset location with respect to an initial location of said medium.

5.   A unitary medium produced by practising a method as claimed in Claim 1.

20 6.   A medium as claimed in Claim 5 and executed as an optically readable disc.

7.   A reader device for interfacing to a medium as claimed in Claim 5.

8.   A device as claimed in Claim 7, and being provided with disc hold means,
25 optical read means and disc drive means for driving a disc track along said optical read means.

9.   A storing device being arranged for practising a method as claimed in Claim 1.